



Jetchem Systems Limited
 Cuba Ind. Est., Ramsbottom, Bury, BL0 0NE
 Tel. 01706 828 888 Fax. 01706 828 000

MATERIAL SAFETY DATA SHEET

Issued : Jan 2009

| | | | | |
|--|-----------|--|-------|--------|
| 1. Product Name: JC010 | | Intended Use: Carbon Deposit Softener / H/D Paint Remover | | |
| 2. Chemical Composition/Information on Ingredients: | | | | |
| Hazardous Ingredient | Index No | % w/w range | WEL | Hazard |
| Sodium Hydroxide | 1310-73-2 | < 30 | 2 ppm | C, R35 |

3. Hazard Identification:

Corrosive. Causes severe burns

| | | | |
|-------------------------------|---|---------------------------------------|--|
| 4. First Aid Measures: | | 11. Toxicological Information: | |
| EYES: | Immediately rinse with clean water for 15 minutes. Obtain immediate medical attention. | EYES: | Severe irritation resulting in serious damage if first aid is not prompt |
| SKIN: | Drench immediately with plenty of water. Remove any contaminated clothing and launder before re-use. Repeatedly apply calcium gluconate gel, Seek urgent medical attention. | SKIN: | Causes severe slow healing burns |
| INGESTION: | Do not induce vomiting. Wash out mouth with water and give water to drink. Obtain urgent medical attention. | INGESTION: | Severe burns and damage to gastro intestinal tract |
| INHALATION: | Remove to fresh air and seek urgent medical attention if symptoms persist. | INHALATION: | Mist or Spray: Severe irritation. Effects may vary with concentration |

| | | | |
|-----------------------------------|-------------------------------------|------------------------------------|-----------------------------------|
| 5. Fire Fighting Measures: | | 12. Ecological Information: | |
| EXTINGUISHING MEDIA: | Foam, carbon dioxide or dry powder. | AQUATIC TOXICITY | Harmful due to pH effects |
| SPECIAL EXPOSURE HAZARDS: | Irritating fumes | BIODEGRADABILITY | Readily biodegradable |
| SPECIAL INSTRUCTIONS: | Wear breathing apparatus. | MOBILITY | Not persistent in the environment |

| | | | |
|---|--|---|--|
| 6. Accidental Release Measures: | | 13. Disposal Considerations: | |
| For large spillage evacuate personnel. Wear personal protection (see sect. 8) | | Use only licensed waste disposal companies. | |
| Do not allow to enter storm drains or water courses. If this occurs inform authorities. | | Rinse empty containers with water. | |
| Contain spillages. Neutralise with alkali and flush to fowl drain with water | | Damage empty containers if disposed of via local waste. | |

| | | | | | |
|---|--|-----------------------------------|------|--|---|
| 7. Handling and Storage: | | 14. Transport Information: | | | |
| Avoid contact with eyes and skin. Avoid breathing mist or spray. Keep away from aluminium and other light alloys. | | UN | 1719 | CLASS | 8 |
| 8. Personal Protection: | | UN Description: | | TRANS CAT | 2 |
| | | | | Corrosive liquid NOS contains sodium hydroxide | |

| | | | | | |
|----------|---|---------------|---------------------------------|------------------------------------|--------------------------|
| GOGGLES | Safety glasses, goggles or full-face visor. | APRONS | Yes if danger of splashing. | 15: Regulatory Information: | |
| GLOVES | Impervious (pvc) gloves | RESPIRATORS | Yes if STEL or OEL is exceeded. | SYMBOL: | CORROSIVE |
| OVERALLS | Yes if danger of splashing. | BARRIER CREAM | Recommended | RISK PHRASES: | R35, Causes severe burns |

| | | | |
|---|---------------------|---|--|
| 9. Physical and Chemical Properties: | | SAFETY PHRASES: | |
| APPEARANCE | Pale Yellow liquid. | S26, in case of contact with eyes rinse immediately with plenty of water and seek medical advice. | |
| ODOUR | Bland | S36/37/38. Wear suitable protective clothing, gloves and eye/face protection | |
| pH | > 13 | | |
| SG | 1.2 (typical). | | |
| FLASH POINT | Not applicable. | | |
| SOLUBILITY | Soluble. | | |

| | | | |
|--|--|---|--|
| 10. Stability and Reactivity: | | 16. Other Information: | |
| Stable under normal conditions. Avoid contact with alkalis, aluminium and other light alloys. Reaction with strong alkalis generates heat. Will react with aluminium and other light alloys to produce flammable hydrogen gas. | | Refer to section 1. No other usage is recommended unless advised in writing by Jetchem Systems Limited | |