

# **INFORMATION / APPLICATION DATA SHEET**

## **PEELABLE COATING (OPAQUE)**

### **JC019**

This product must be used by competent stone cleaning contractors, experienced in the use of solvents.

#### **DATA SHEET**

#### **PRODUCT DESCRIPTION**

JC019 is a fast drying solvent based peelable protective coating designed to protect components and finished articles during handling, manufactured assembly, storage and delivery. It can be used safely on all smooth ferrous metals, plain aluminium, vitreous enamels, ceramics, glass and other non-solvent sensitive surfaces and will protect against abrasion, impact damage, welding spatter, rusting, corrosion, chemical attack, paint resins and bitumen's.

#### **FEATURES AND BENEFITS**

- Speedy application and removal
- Excellent durability
- Offers good abrasion and chemical resistance
- Leaves surface clean on removal

#### **DIRECTIONS FOR USE**

It can be applied by brush, spray, lambs wool or mohair roller ensuring that heavy even coats are applied. The thicker and more even the application the easier it will be to remove after service. If a brush or roller coating is used at least two coats in opposite directions is required to achieve the correct thickness. When applying by spray use a pressure feed system and approximately a 70 thou fluid tip (1.78mm) set up at the gun. It may be necessary to add approximately 10-15% 6118 THINNERS LF to ease spraying. These thinners will also be necessary for cleaning of equipment after use. Do not use suction feed guns.

#### **COVERAGE**

Approximately 1-2 square metres per litre to achieve 4-8 thou dry film thickness. Thinner films than this must not be applied. Do not apply to solvent sensitive or porous surfaces such as painted or lacquered window frames, painted, plastic or wooden surfaces of any kind. Application to anodised aluminium surfaces may require thicker films to ensure peelability.

This depends on the degree of anodising and must be patch tested first. For outdoor applications a minimum thickness of 8 thou is recommended. If in any doubt carry out a patch test and get technical advice before carrying out the work.

Continued...

JC019

- 2 -

## **FIRST AID**

Splashes to the Skin: Can be peeled off, the solvents may cause skin irritation.

Splashes to the Eyes: Irrigate with clean water for at least 5 to 15 minutes changing water frequently.

## **ECOLOGY**

This product will adhere to rough surfaces such as brick or sandstone, plants and shrubs should be protected with plastic sheeting. After the flammable solvents have evaporated the coating remaining is non injurious and can be disposed of as normal solid waste, no soluble chemicals are removed from the coating.

## **LIFE**

For the applied film a maximum life of six months is recommended under UK outdoor conditions but inspection after three months is advised. For longer periods than six months the coating should be removed and reapplied. Under indoor conditions in the absence of direct sunlight up to twelve months is normally achieved at the recommended film thickness.

## **SPECIAL STORAGE**

Store in a cool place, complying with the Petroleum Consolidation Act 1928 and Amendments or Local and National Highly Flammable Liquids Regulations.

## **WARNING**

Solvent based peelable coatings are not generally suitable for application to painted, plastic, or lacquered surfaces, and MUST be carefully patch tested before use to ensure no surface attack occurs and the product remains easily peelable after normal usage conditions.

Any use of these products on solvent sensitive surfaces where natural evaporation of the solvent may be retarded can lead to aggravated solvent attack, for instance, seepage under a mask.

## **HEALTH AND SAFETY**

This product is highly flammable and harmful, please refer to our separate Health & Safety Data Sheet for complete details.

Continued...

JC019

- 3 -

### **Regulatory Information**

Consult the Material Safety Data Sheet covering this product for the chemical composition and information on ingredients.

The information provided here does not constitute the users own assessment of workplace risks as required by the Health & Safety legislation.

NO GUARANTEE IS MADE TO THE ACCURACY OF ANY DATA OR STATEMENT CONTAINED HEREIN. WHILE THIS IS FURNISHED IN GOOD FAITH, NO WARRANTY EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE IS MADE.

For further information regarding the product contact (01706) 828888 or Fax: (01706) 828000  
**Jetchem Systems Limited, Cuba Industrial Estate, Bolton Road North, Ramsbottom, Bury Lancashire, BL0 0NE**

Revision : January 2009